	TANKO CHARTERING QUESTIONNAIRE 88 - OIL	Version 5
1.	GENERAL INFORMATION	
1.1	Date updated:	Dec 16, 2022
1.2	Vessel's name (IMO number):	Ottoman Equity (9404950)
1.3	Vessel's previous name(s) and date(s) of change:	Not Applicable
1.4	Date delivered/Builder (where built):	Dec 01, 2008/HHI Ulsan S.Korea
1.5	Flag/Port of Registry:	Turkey/ISTANBUL
1.6	Call sign/MMSI:	TCTG7/271002613
1.7	Vessel's contact details (satcom/fax/email etc.):	Tel: +870 773 910869 / +90 212 9702686 Fax: Email: equity@gungen.com
1.8	Type of vessel (as described in Form A or Form B Q1.11 of the IOF	
1.9	Type of hull:	Double Hull
	rship and Operation	
		CUNCTN DENIZOU WAS TICADET A C
1.10	Registered owner - Full style:	GUNGEN DENIZCILIK VE TICARET A.S. HALICI SOKAK NO:9 GOP 06700 ANKARA/TURKEY Turkey Tel: +90(312)455 35 35 Fax: +90(312)455 35 25 Email: vetting@gungen.com Web: www.gungen.com
1.11	Technical operator - Full style:	GUNGEN DENIZCILIK VE TICARET A.S. HALICI SOKAK NO: 9 G.O.P. 06700 ANKARA - TURKEY Turkey Tel: +90(216) 556 56 56 Fax: +90 216 556 56 66 Telex: 44111 or 44666 Email: vetting@gungen.com Web: www.gungen.com Company IMO#: 1366389
1.12	Commercial operator - Full style:	GÜNGEN DENIZCILIK VE TICARET ANONIM SIRKETI Halici Sokak. No:9 Gaziosmanpasa-06700 Ankara-TÜRKIYE Turkey Tel: +90(216) 556 56 56 Fax: +90 216 556 56 66 Email: tankerops@gungen.com Web: www.gungen.com
1.13	Disponent owner - Full style:	GÜNGEN DENIZCILIK VE TICARET ANONIM SIRKETI GUNGEN DENIZCILIK VE TICARET ANONIM SIRKETI HALICI SOKAK NO.9 GOP ANKARA/TURKEY Tel: +90(312) 455 35 35 Fax: +90 (312) 455 35 25 Telex: 44111 or 44666 Email: vetting@gungen.com Tel: +90(216) 556 56 56 Fax: +90 216 556 56 66 Telex: Telex: 44111 or 44666 Email: tankerops@gungen.com Web: www.gungen.com
Insura	ance	
1.14	P & I Club - Full Style:	UK P&I CLUB 90 Fenchurch Street br/>London EC3M 4ST Tel: 0044 020 7283 4646 Email: underwriting.ukclub@thomasmiller.com
1.15	P & I Club pollution liability coverage/expiration date:	1,000,000,000 US\$ Feb 20, 2023
1.16	Hull & Machinery insured by - Full Style: (Specify broker or leading underwriter)	Lockton Companies LLP The St Botolph Building 138 Houndsditch London EC3A 7AG M: +44 (0)7585881327 E: jack.farley@lockton.com

	Tel: +44 (0)20 7933 2468				
1.17	Hull & Machinery insured value/expiration date:			50,000,000 US\$	Nov 22, 2024
Classif	ication			1	
1.18	Classification society:			Det Norske Veritas	
1.19			+1A1, Tanker for oil, BWM (T) CCO, Clean, COAT-1, CSR, EO, ESP, ICS, OPP-F, Plus(1), SPM, TMON, VCS(2, B), BMON		
1.20	Is the vessel subject to any conditions of class, class exten class recommendations? If yes, give details:	sions, outstanding m	emorandums or	No N/A	
1.21	If classification society changed, name of previous and da	te of change:		N/A, Not Applicable	
1.22	Does the vessel have ice class? If yes, state what level:			No, N/A	
1.23	Date/place of last dry-dock:			Jan 09, 2019/SINGAP	ORE
1.24	Date next dry dock due/next annual survey due:			Dec 01, 2023	
1.25	Date of last special survey/next special survey due:			Jan 09, 2019	
1.26	If ship has Condition Assessment Program (CAP), what is t	he latest overall ratin	g:	No,	
Dimen	sions				
1.27	Length overall (LOA):				269.17 Metres
1.28	Length between perpendiculars (LBP):				258.00 Metres
1.29	Extreme breadth (Beam):				46.04 Metres
1.30	Moulded depth:				24.40 Metres
1.31	Keel to masthead (KTM)/ Keel to masthead (KTM) in colla	psed condition, if app	licable:	52.18 Metres	50.65 Metres
1.32	Distance bridge front to center of manifold:				91.00 Metres
1.33	Bow to center manifold (BCM)/Stern to center manifold (SCM):		133.12 Metres	136.05 Metres
1.34	Parallel body distances		Lightship	Normal Ballast	Summer Dwt
	Forward to mid-point manifold:		62.30 Metres	66.60 Metres	66.50 Metres
	Aft to mid-point manifold:		32.90 Metres	48.40 Metres	69.30 Metres
	Parallel body length:		95.20 Metres	115 Metres	135.80 Metres
Tonna	ges				
1.35	Net Tonnage:				48,517.00
1.36	Gross Tonnage/Reduced Gross Tonnage (if applicable):			79,934.00	63,819
1.37	Suez Canal Tonnage - Gross (SCGT)/Net (SCNT):			82,203.13	77,201.34
1.38	Panama Canal Net Tonnage (PCNT):				
Loadli	ne Information				
1.39	Loadline	Freeboard	Draft	Deadweight	Displacement
	Summer:	6.963 Metres	17.476 Metres	149,999.00 Metric Tonnes	174,742 Metric Tonnes
	Winter:	7.327 Metres	17.112 Metres	146,001.10 Metric Tonnes	170,744.00 Metric Tonnes
	Tropical:	6.599 Metres	17.84 Metres	154,005.10 Metric Tonnes	178,748.00 Metric Tonnes
	Lightship:	21.605 Metres	2.834 Metres	-	24,742.90 Metric Tonnes
	Normal Ballast Condition:	16.63 Metres	9.11 Metres	46,834 Metric Tonnes	71,577 Metric Tonnes
	Segregated Ballast Condition:	15.83 Metres	9.56 Metres	55,329 Metric Tonnes	80,072 Metric Tonnes
1.40	FWA/TPC at summer draft:			398.00 Millimetres	109.98 Metric Tonnes
1.41	Does vessel have multiple SDWT? If yes, please provide al	l assigned loadlines:		No	
1.42	Constant (excluding fresh water):				100 Metric Tonnes

1.43	What is the company guidelines for Under Keel Clearance (UKC) for this vessel?	1-OCEAN AND OPEN SUMMER DRAUGHT 2-PORT LIMITS, APPR CHANNELS, CANALS, WHILE ALONGSIDE: 1 BREADTH OF THE VESTHAN 0.7 METERS	OACHES, FAIRWAYS, RIVERS, SBM/CBM, .5% OF MOULDED
1.44	What is the max height of mast above waterline (air draft)	Full Mast	Collapsed Mast
	Summer deadweight:	34.704 Metres	33.174 Metres
	Normal ballast:	42.62 Metres	41.09
	Lightship:	49.346 Metres	47.816 Metres

2.	CERTIFICATES	Issued	Last Annual	Last Intermediate	Expires
2.1	Safety Equipment Certificate (SEC):	Oct 14, 2021	Oct 14, 2021		Dec 01, 2023
2.2	Safety Radio Certificate (SRC):	Oct 14, 2021	Oct 14, 2021		Dec 01, 2023
2.3	Safety Construction Certificate (SCC):	Oct 14, 2021	Oct 14, 2021		Dec 01, 2023
2.4	International Loadline Certificate (ILC):	Oct 14, 2021	Oct 14, 2021		Dec 01, 2023
2.5	International Oil Pollution Prevention Certificate (IOPPC):	Oct 14, 2021	Oct 14, 2021		Dec 01, 2023
2.6	International Ship Security Certificate (ISSC):	Feb 26, 2019		Feb 26, 2019	Apr 09, 2024
2.7	Maritime Labour Certificate (MLC):	Oct 16, 2021	N/A		May 08, 2023
2.8	ISM Safety Management Certificate (SMC):	Feb 26, 2019		Feb 26, 2019	Apr 29, 2024
2.9	Document of Compliance (DOC):	Apr 02, 2021			Apr 05, 2026
2.10	USCG Certificate of Compliance (USCGCOC):	Jan 17, 2017			Jan 17, 2018
2.11	Civil Liability Convention (CLC) 1992 Certificate:	Feb 20, 2022	N/A	N/A	Feb 20, 2023
2.12	Civil Liability for Bunker Oil Pollution Damage Convention (CLBC) Certificate:	Feb 20, 2022	N/A	N/A	Feb 20, 2023
2.13	Liability for the Removal of Wrecks Certificate (WRC):	Feb 20, 2022	N/A	N/A	Feb 20, 2023
2.14	U.S. Certificate of Financial Responsibility (COFR):	Dec 02, 2020	N/A	N/A	Oct 12, 2023
2.15	Certificate of Class (COC):	Oct 14, 2021	Oct 14, 2021		Dec 01, 2023
2.16	International Sewage Pollution Prevention Certificate (ISPPC):	Oct 14, 2021	N/A	N/A	Dec 01, 2023
2.17	Certificate of Fitness (COF):	Not Applicable	Not Applicable		Not Applicable
2.18	International Energy Efficiency Certificate (IEEC):	Oct 14, 2021	N/A	N/A	N/A
2.19	International Air Pollution Prevention Certificate (IAPPC):	Oct 14, 2021	Oct 14, 2021		Dec 01, 2023
Docun	nentation				
2.20	Owner warrant that vessel is member of ITOPF and will remain so for the entire duration of this voyage/contract:		Ye	es	
2.21	Does vessel have in place a Drug and Alcohol Policy complying with OCIMF guidelines for Control of Drugs and Alcohol Onboard Ship?		Ye	Yes	
2.22	22 Is the ITF Special Agreement on board (if applicable)?			N/	/A
2.23	ITF Blue Card expiry date (if applicable):			Not App	olicable

3.	CREW				
3.1	Nationality of Master:			Turkish	
3.2	Number and nationality of Officers:		Turkish		
3.3	Number and nationality of Crew:		19	Turkish	
3.4	What is the common working language onboard:			Turkish, English	
3.5	Do officers speak and understand English?			Yes	
3.6	If Officers/ratings employed by a manning agency - Full style:	Officers: see Registe	ered Owner	Ratings: see Registered Owner	

4.	FOR USA CALLS
----	---------------

4.1	Has the vessel Operator submitted a Vessel Spill Response Plan to the US Coas been approved by official USCG letter?	st Guard which has Yes	
4.2		ECM Maritime Services, LLC 1 Selleck Street – 1st Floor, Suite 1C Tel: +1.203.857.0444 or +1.281.464.3328 Fax: +1-203-857-0428 Email: QI@ecmmaritime.com	
4.3		Marine Spill Response Corp. (MSRC) 220 Spring Street, Suite 500 Herndon, VA 20170 Tel: +1-800-259-6772 or +1-703-326-5609 Fax: +1-703-326-5660	
4.4	Salvage and Marine Firefighting Services (SMFF) - Full Style:		

5.	SAFETY/HELICOPTER	
1	1	Yes ISO 9001 and IMO Resolution A.741 (18)
5.2	Can the ship comply with the ICS Helicopter Guidelines?	Yes
5.2.1	If Yes, state whether winching or landing area provided:	Landing
5.2.2	If Yes, what is the diameter of the circle provided:	13.00 Metres

6.	COATING/ANODES				
6.1	Tank Coating	Coated	Туре	To What Extent	Anodes
	Cargo tanks:	Yes	Pure Epoxy	Deck head to 3m below & Bottom to 0.5m upwards	No
	Ballast tanks:	Yes	Ероху	Fully	Yes
	Slop tanks:	Yes	Pure Epoxy	Whole Tank	Yes

7.	BALLAST				
7.1	Pumps	No.	Туре	Capacity	At What Head (sg=1.0)
	Ballast Pumps:	2	Centrifugal	2,500 Cu. Metres/Hour	30 Metres
	Ballast Eductors:	1	TEAMTEC-GOLAR	200 Cu. Metres/Hour	25 Metres

8.	CARGO					
Double	Double Hull Vessels					
8.1	Is vessel fitted with centerline bulkhead in all cargo tanks? If Yes, solid or perforated:	Yes, Solid				
Cargo	Tank Capacities					
8.2	Number of cargo tanks and total cubic capacity (max% per company policy: 98%, 97%, 96% or 95%) excluding slops tanks:	12	166,671 Cu. Metres			
8.2.1	Capacity (max% per company policy: 98%, 97%, 96% or 95%) of each natural segregation with double valve (specify tanks):	Seg#1: 55217.0 m3 (1,4, & Slops (P&S)) Seg#2: 58222.8 m3 (2 & 5 (P&S)) Seg#3: 56136.4 m3 (3 & 6 (P&S))				
8.2.2	IMO class (Oil/Chemical Ship Type 1, 2 or 3):					
8.3	Number of slop tanks and total cubic capacity (max% per company policy: 98%, 97%, 96% or 95%):	2	2,905.40 Cu. Metres			
8.3.1	Specify segregations which slops tanks belong to and their capacity with double valve:	1st, 2.905,4 Cu. Met	res			
8.3.2	Residual/retention oil tank(s) capacity (98%), if applicable:					
SBT Ve	essels					
8.3.3	What is total SBT capacity and percentage of SDWT vessel can maintain?	52,269 Cu. Metres	34.70 %			

8.3.4	Does vessel meet the requirements of MARPOL Annex I Reg 18.2:	Yes		
Cargo	Handling and Pumping Systems			
8.4	How many grades/products can vessel load/discharge with double valve segregation:		3	
8.5	Are there any cargo tank filling restrictions? If yes, specify number of slack tanks, max s.g., ullage restrictions etc.:	Yes 1,025 kg/lt cargo density		
8.6	Max loading rate for homogenous cargo	With VECS	Without VECS	
	Loaded per manifold connection:	7,720 Cu. Metres/Hour	7,720 Cu. Metres/Hour (7,720 cbm/h, with one manifold, 15,440 cbm/h, with two manifolds 17,000 cbm/h, with three manifolds)	
	Loaded simultaneously through all manifolds:	17,000 Cu. Metres/Hour	17,000 Cu. Metres/Hour	
	Control Room			
8.7	Is ship fitted with a Cargo Control Room (CCR)?		es	
8.8	Can tank innage/ullage be read from the CCR?	Y	es	
	ng and Sampling			
8.9	Is gauging system certified and calibrated? If no, specify which ones are not calibrated:	Yes,		
	What type of fixed closed tank gauging system is fitted:	Radar beam type level gauge		
0.0.4	Are high level alarms fitted to the cargo tanks? If Yes, indicate whether to all tanks or partial:	Yes, All		
8.9.1	Can cargo be transferred under closed loading conditions in accordance with ISGOTT 11.1.6.6? Are cargo tanks fitted with multipoint gauging? If yes, specify type and locations:	Yes Yes, 3 vapour locks, 1 each aft, mid and forward		
8.10	Number of portable gauging units (example- MMC) on board:		2	
Vapor	Emission Control System (VECS)			
8.11	Is a vapour return system (VRS) fitted?	Yes		
8.12	Number/size of VECS manifolds (per side):	2	406.40 Millimetres	
8.13	Number/size/type of VECS reducers:	2x304.8 Millimeters 1x254.0 Millimeters		
Ventin	ng e			
8.14	State what type of venting system is fitted:	VENT RISER + HIGH \	/ELOCITY PV VALVES	
Cargo	Manifolds and Reducers			
8.15	Total number/size of cargo manifold connections on each side:	3/609.60 Millimetre	5	
8.16	What type of valves are fitted at manifold:	Butterfly		
8.17	What is the material/rating of the manifold:	CAST STEEL/ANSI B1		
8.17.1	Does vessel comply with the latest edition of the OCIMF 'Recommendations for Oil Tanker Manifolds and Associated Equipment'?	Y	es	
8.18	Distance between cargo manifold centers:		2,500.00 Millimetres	
8.19	Distance ships rail to manifold:		4,600.00 Millimetres	
8.20	Distance manifold to ships side:		4,600.00 Millimetres	
8.21	Top of rail to center of manifold:		780.00 Millimetres	
8.22	Distance main deck to center of manifold:		2,100.00 Millimetres	
8.23	Spill tank grating to center of manifold:		900.00 Millimetres	
8.24 8.25	Manifold height above the waterline in normal ballast/at SDWT condition: Number/size/type of reducers:	18.74 Metres 3 x 609.6/406.4mm 3 x 609.6/304.8mm 3 x 609.6/254mm (2 3 x 609.6/203.2mm ANSI	(24/12") 4/10")	
8.26	Is vessel fitted with a stern manifold? If yes, state size:	No,		

Heatir	ng				
8.27	Cargo/slop tanks fitted with a cargo heating sys	Туре	Coiled	Material	
	Cargo Tanks:	Steam	Yes	Other	
	Slop Tanks:	Heating Coils	Yes	STPG 370S (Carbon Steel)	
8.28	Maximum temperature cargo can be loaded/m	aintained:	<u>.</u>	66.0 °C / 150.8 °F	66 °C / 150.8 °
8.28.1	Minimum temperature cargo can be loaded/ma	aintained:		0.0 °C / 32.0 °F	0.0 °C / 32.0 °
Inert (Gas and Crude Oil Washing				
8.29	Is an Inert Gas System (IGS) fitted/operational?	Yes/Yes			
8.29.1	Is a Crude Oil Washing (COW) installation fitted	Yes/Yes			
8.30	Is IGS supplied by flue gas, inert gas (IG) genera	Flue Gas			
Cargo	Pumps				
8.31	How many cargo pumps can be run simultaneously at full capacity:				:
8.32	Pumps	No.	Туре	Capacity	At What Head (sg=1.0)
	Cargo Pumps:	3	Centrifugal	4000 M3/HR	135 Meter 135 Meter 135 Meter
	Cargo Eductors:	2	TEAMTEC-GOLAR	470 Cu. Metres/Hour	25 Metre
	Stripping:	1	Reciprocating	250 Cu. Metres/Hour	135 Metre
8.33	Is at least one emergency portable cargo pump	provided?			

9.	MOORING					
9.1	Wires (on drums)	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:			Not Applicable		
	Main deck fwd:			Not Applicable		
	Main deck aft:			Not Applicable		
	Poop deck:			Not Applicable		
9.2	Wire tails	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	4	76 Millimetres	POLYESTER	11.00 Metres	108 Metric Tonnes
	Main deck fwd:	4	76 Millimetres	POLYESTER	11.00 Metres	108 Metric Tonnes
	Main deck aft:	2	76 Millimetres	POLYESTER	11.00 Metres	108 Metric Tonnes
	Poop deck:	6	76 Millimetres	POLYESTER	11.00 Metres	108 Metric Tonnes
9.3	Ropes (on drums)	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	4	34.00 Millimetres	HMPE (High Modulus Poly Ethylene)	280.00 Metres	83.90 Metric Tonnes
	Main deck fwd:	4	34.00 Millimetres	HMPE (High Modulus Poly Ethylene)	280.00 Metres	83.90 Metric Tonnes
	Main deck aft:	2	34.00 Millimetres	HMPE (High Modulus Poly Ethylene)	280.00 Metres	83.90 Metric Tonnes
	Poop deck:	6	34.00 Millimetres	HMPE (High Modulus Poly Ethylene)	280.00 Metres	83.90 Metric Tonnes
9.4	Other lines	No.	Diameter	Material	Length	Breaking Strength
	Forecastle:	3	72 Millimetres	POLYESTER	220 Metres	86 Metric Tonnes
	Main deck fwd:			Not Applicable		
	Main deck aft:			Not Applicable		
	Poop deck:	3	72 Millimetres	POLYESTER	220 Metres	86 Metric Tonnes

9.5	Winches	No.	No. Drums	Motive Power	Brake Capacity	Type of Brake
	Forecastle:	2	Double Drums	Hydraulic		Hydraulic controlled brake lining
	Main deck fwd:	2	Double Drums	Hydraulic		Hydraulic controlled brake lining
	Main deck aft:	1	Double Drums	Hydraulic		Hydraulic controlled brake lining
	Poop deck:	3	Double Drums	Hydraulic		Hydraulic controlled brake lining
9.6	Bitts, closed chocks/fairleads		No. Bitts	SWL Bitts	No. Closed Chocks	SWL Closed Chocks
	Forecastle:		5	84 Metric Tonnes	6	84 Metric Tonnes
	Main deck fwd:		10	84 Metric Tonnes	12	84 Metric Tonnes
	Main deck aft:		5	84 Metric Tonnes	6	84 Metric Tonnes
	Poop deck:		5	84 Metric Tonnes	12	84 Metric Tonnes
Ancho	rs/Emergency Towing System		•	•		
9.7	Number of shackles on port/starboard cable:				13	/14
9.8	Type/SWL of Emergency Towing system forwar	KETA-45F CHAFING CHAIN	350 Metric Tonnes			
9.9	Type/SWL of Emergency Towing system aft:				KETSP-40A	200 Metric Tonnes
9.10.1	What is size of closed chock and/or fairleads of	enclosed	type on stern			1160 X 504 X 1130
Escort	Tug					
9.10.2	What is SWL of closed chock and/or fairleads o	f enclosed	type on stern:			200.00 Metric Tonnes
9.11	What is SWL of bollard on poop deck suitable for	or escort t	ug:		200.00 Metric Tonnes	
Lifting	Equipment/Gangway					
9.12	Derrick/Crane description (Number, SWL and Id	ocation):			Derricks: 0.00 Tonner Tonnes 2 Derricks Onboard 1 x 0.1 tons 1 x 0.2 tons 3 Cranes Onboard 1 x 15 tons (center) 1 x 5 tons (port) 1 x 2 tons (starboard	
9.13					Aft	
	Does vessel have a portable gangway? If yes, st	ate length	:			Yes, 16 Metres
Single	Point Mooring (SPM) Equipment				1	,
9.14	Does the vessel meet the recommendations in the latest edition of OCIMF 'Recommendations for Equipment Employed in the Bow Mooring of Conventional Tankers at Single Point Moorings (SPM)'?			Υ	es	
9.15	f fitted, how many chain stoppers:			2		
9.16	State type/SWL of chain stopper(s):			TONGUE SM490	350 Metric Tonnes	
9.17	What is the maximum size chain diameter the b	What is the maximum size chain diameter the bow stopper(s) can handle:				76 Millimetres
9.18	Distance between the bow fairlead and chain s	topper/bra	acket:		3.15 Metres	
9.19	Is bow chock and/or fairlead of enclosed type of OCIMF recommended size (600mm x 450mm)? If not, give details of size:			Yes Not Applicable		

10.	PROPULSION		
10.1	Speed	Maximum	Economical
	Ballast speed:	15 Knots (WSNP)	11 Knots (WSNP)
	Laden speed:	14.50 Knots (WSNP)	11 Knots (WSNP)
10.2	What type of fuel is used for main propulsion/generating plant:	VLSFO, LSMGO	VLSFO, LSMGO
10.3		Fuel Oil: 2,882.80 Cu. Metres Diesel Oil: 1,018.80 Cu. Metres Gas Oil: 0 Cu. Metres	

10.4	4 Is vessel fitted with fixed or controllable pitch propeller(s):		None	
10.5	Engines	No	Capacity	Make/Type
	Main engine:	1	16,780 Kilowatt	HYUNDAI Man B&W 6S70ME-C
	Aux engine:	3	960 Kilowatt	Himsen (6H 21/32)
	Power packs:			
	Boilers:	2	40.00 Metric Tonnes/Hour	Alborg/MISSION OM
Bow/S	Stern Thruster	<u>.</u>		
10.6	What is brake horse power of bow thruster (if fitted):		No, 0 bhp	
10.7	What is brake horse power of stern thruster (if fitted):		No,	
Emiss	ions			
10.8	Main engine IMO NOx emission standard:		Tier I	
10.9	9 Energy Efficiency Design Index (EEDI) rating number:		3,234	

11.	SHIP TO SHIP TRANSFER		
1	Does vessel comply with recommendations contained in OCIMF/ICS Ship To Ship Transfer Guide (Petroleum, Chemicals or Liquified Gas, as applicable)?	Yes	
11.2	What is maximum outreach of cranes/derricks outboard of the ship's side:	7.00 Metres	
11.3	Date/place of last STS operation:		

12.	RECENT OPERATIONAL HISTORY	
12.1	Last three cargoes/charterers/voyages (Last/2nd Last/3rd Last):	
12.2	Has vessel been involved in a pollution, grounding, serious casualty, unscheduled repair or collision incident during the past 12 months? If yes, provide details:	Pollution: No, n/a Grounding: No, n/a Casualty: No, n/a Repair: No, Not Applicable Collision: No, n/a
12.3	Date and place of last Port State Control inspection:	
12.4	Any outstanding deficiencies as reported by any Port State Control? If yes, provide details:	No n/a
12.5	Recent Oil company inspections/screenings (To the best of owners knowledge and without guarantee of acceptance for future business)*: * "Approvals" are not given by Oil Majors and ships are accepted for the voyage on a case by case basis.	
12.6	Date/Place of last SIRE inspection:	
12.7	Additional information relating to features of the ship or operational characteristics:	

Revised 2018 (INTERTANKO/Q88.com)

Form completed on http://www.q88.com/integration.aspx Please email support@q88.com an updated copy if this is not the latest version.

To the best of owners knowledge all information is true and given without any guarantee.